



TASKI®

Millentra



F2

Low to Medium Speed Floor Finish

Description

TASKI® Millentra is an economical scrub and recoat floor finish for use on all internal resilient floors such as vinyl and porous composite tiles. TASKI® Millentra resists scuffing, dirt and marking to extend the recoat cycle.

Precautions

- Do not dilute.
- Do not use on surfaces colder than 10°C/50°F.
- To avoid contamination, do not return unused finish to original container.
- Not intended for outdoor use.

Features

- Can be used as a scrub and recoat finish.
- Resists scuffing, dirt and marking.
- TASKI® Millentra gives high levels of gloss, durability and levelling with good colour stability.
- Economical and suitable for most types of floors.
- Easy to maintain low to medium speed finish.
- Use with 175-900 rpm for best results.

Benefits

- TASKI® Millentra's resilience and scuff resistance reduces the need for recoats saving time and labour.
- Resists black heel marks, scuffs, detergents and scrubbing.
- Responds well to spray buffing which means floor will retain its gloss for longer between recoats.

Application areas

- Retail
- Education
- Government
- Healthcare
- Institutional Facilities





TASKI®

Millentra



F2

Directions for use

Blockade areas to be stripped or finished. Floors will be very slippery until dry. Position wet-floor signs around area to be cleaned.

Application:

1. Strip floor using recommended Diversey brand stripper according to label directions.
2. Apply 2-3 uniform coats using a clean mop. If higher gloss is desired apply additional coats.
3. Allow 30 minutes drying time between coats. Temperature, humidity and ventilation may affect drying time.

Maintenance:

1. Dust, mop or sweep.
2. Clean floor using recommended Diversey cleaner according to label directions.
3. If desired, spray buff using Diversey brand floor maintainer to enhance gloss.

Before Recoating:

1. Dust, mop or sweep.
2. Deep scrub floor using recommended Diversey brand cleaner according to label directions.
3. Apply 1-2 coats using a clean mop.

Coverage: 50-60m² per litre.

Technical data			
Appearance	Milky white liquid	Specific gravity	1.03
Odour	Characteristic odour	pH (concentrate)	8.5
Dilution	Neat	Slip classification	Class F (AS/NZS 4586-2004)
Maintenance speed	175 – 900 rpm		

The above data is typical of normal production and should not be taken as a specification.

Product	Pack size	SKU Code	Availability
TASKI® Millentra	2 x 5L	5687497	AU
TASKI® Millentra	200L	HH15097	AU

Safe handling and storage information

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet. Store in original container. Avoid extremes of temperature and humidity.

Product compatibility

Under recommended conditions of use, TASKI® Millentra is suitable for use on most floor types. Non-resilient (porous) floors must be sealed first before applying finish. Ideal for low maintenance, spray buffing program.

Safety Reminder

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use, and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDSs are available online at www.diversey.com or by calling Toll free: Australia, 1800 647 779 or New Zealand, 0800 803 615.

For additional information, please contact us at:
Diversey Australia Pty Ltd Toll free: 1800 647 779, Diversey New Zealand Ltd Toll free: 0800 803 615 www.diversey.com.

© 2018 Diversey, Inc. All Rights Reserved. Legal disclaimer: The associated products or services are manufactured by or otherwise emanate from Diversey Companies and their subsidiaries and not from Sealed Air.