



TASKI®

Pro Strip™ HD



Stripper

Description

TASKI® Pro Strip HD is a high performance stripper for the removal of tough sealer finishes. TASKI® Pro Strip HD is formulated for rapid bite in and deep penetration of multiple layers of sealer/finishes found in UHS floorcare programs including vinyl composite tile, terrazzo and concrete floors.

Reduce labour

- TASKI® Pro Strip HD is formulated for rapid bite in and deep penetration of multiple layers of sealer finishes from vinyl composite tile, terrazzo and concrete floors.
- Powerful dual action stripper containing alkalis and solvents.
- Removes both metalised and non-metalised floor finishes.

Excellent performance

- Works in cool water.
- Variable dilution rate to match the job.
- Effective on a wide range of sealer/finishes.

Application areas

- Retail
- Education
- Government
- Healthcare
- Institutional Facilities





TASKI®

Pro Strip™ HD



Directions for use

1. Dust, mop with or sweep to remove dust or dirt.
2. Dilute 1 part TASKI® Pro Strip HD with 4 -10 parts of cool to warm water depending on build up.
3. Apply liberal amounts of solution to the surface to be stripped.
4. Let stripper solution soak in for 5-10 minutes. Keep areas to be stripped wet.
5. Scrub thoroughly using swing or stripping machine with a stripping pad or brush to break up film.
6. Manually strip areas that cannot be reached with the machine.
7. Pick-up all of the solution with a clean mop, wet vac or auto scrubber. Trail mop as needed if stripper residues are present.
8. Rinse floor with clean water using clean mop and bucket or auto scrubber if stripper residues are present.
9. Let floor dry completely.
10. Inspect floor for any areas requiring further stripping.
11. Wash out all equipment before storage.

In New Zealand: MPI Approved C 25 (All animal product except dairy).

Technical data			
Appearance	Clear pale yellow liquid	Specific Gravity (20°C)	1.025
Odour	Solvent odour	pH (concentrate)	>12.5
Coverage	30 – 60m ² per litre Depending on polish build up	Dilution	1:10 (Light build up) 1:4 (Heavy build up)
pH (use dilution)	12.5 (1:4, 1:10)		

The above data is typical of normal production and should not be taken as a specification.

Product	Pack size	SKU Code	Availability
TASKI® Pro Strip HD	2 x 5L	5751137	AU & NZ

Safe handling and storage information

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet. Store in original container. Avoid extremes of temperature and humidity.

Product compatibility

Under recommended conditions of use, TASKI® Pro Strip HD is suitable to remove polish on vinyl composite tile, terrazzo and concrete floors. Not suitable to remove polish on linoleum, rubber and wooden floors. If using for the first time, try on a small area first before working on the entire area.

Safety Reminder

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use, and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDSs are available online at www.diversey.com or by calling Toll free: Australia, 1800 647 779 or New Zealand, 0800 803 615.

For additional information, please contact us at:
Diversey Australia Pty Ltd Toll free: 1800 647 779, Diversey New Zealand Ltd Toll free: 0800 803 615 www.diversey.com.

© 2018 Diversey, Inc. All Rights Reserved. Legal disclaimer: The associated products or services are manufactured by or otherwise emanate from Diversey Companies and their subsidiaries and not from Sealed Air.