

CAREFREE Showplace

High gloss floor emulsion

Description

High-gloss, slip-resistant floor emulsion for most types of smooth and water resistant, hard floors.

Its technology gives superior traffic resistance against scuffs and dirt. It ensures reduced maintenance costs to improve productivity. Easy to apply, it will be ideal in all prestige and heavy traffic areas where ordinary emulsions require a high level of maintenance.

Key properties

- High-gloss, protective layer
- Hard, durable and wear resistant protection
- Easy to apply, short drying time
- Slip resistant according to international standards (ASTM D-2047)
- Easy to repair

Benefits

- Enhances the natural appearance of the floor by providing a long lasting high gloss finish
- Superior resistance to scuff marks and dirt, even under heavy traffic
- Excellent adhesion on most floor types such as vinyl, synthetic, linoleum, stone, sealed wood and cork floors. Can be applied with a mop or an applicator. Spreads evenly for perfect levelling
- Guaranteed safety for your employees and customers
- Responds to most common maintenance methods

Use instructions

Dosage:

The product is ready to use. Apply undiluted

Application:

Treat only stripped and thoroughly rinsed and completely dry floors.


Treat porous and damaged floors with a sealer prior to application. Sparingly pour the product onto the floor and evenly spread it while still wet with a polish applicator in overlapping lanes of 1-1.5m. Allow to dry completely (20-30 minutes) before applying additional coats in a similar manner. Apply two coats to non-porous, smooth floors. Three coats are usually sufficient for porous floors.

Linoleum: After the first coat has dried, smooth the linoleum floor with a single disc machine equipped with a bluepad, then damp mop and allow to dry completely before applying additional coats.

Important:

Do not dilute or mix with other substances.

Do not use on structured plastic (cushioned vinyl) and unsealed wood or cork. Seek advice for use on profiled/studded rubber floors. Do not use outdoors or in wet zones.



CAREFREE Showplace

Technical data

- Appearance: Milky white liquid
- Relative density [20°C]: 1.04
- pH-value neat: 8.2 - 8.7
- Coverage: 20-40 ml/m²

The above data is typical of normal production and should not be taken as a specification.

Safe handling and storage information

Safe handling:

Full guidance on the handling and disposal of this product is provided in a separate Material Safety Data Sheet. Only for professional users / specialists.

Storage Information:

Store in original closed containers and do not store at temperatures below 5°C

Approvals

Tested according to ASTM D-2047 for slip resistance

Available pack sizes

- 1 x 5L
- 1 x 20L

Diversey Eastern and Central Africa Ltd

Kaptagat Road, Loresho
P.O Box 41939 - 00100 Nairobi
Tel.+254(20)4224000 3008000
Fax:+254(20)4224888 / 4180481
www.diversey.com